

**POLYCAB**

IDEAS. CONNECTED.

**POLYCAB INDIA LIMITED****PCC LP No. 03/2026-27 Dtd : 1st June 2026****List of Products Covered in Our PCC LP****Aluminium Armoured / Unarmoured Cables****Copper Armoured / Unarmoured Cables****HT Cables****1.9 KV / 3.3 KV Cables for Solar****Instrumentation Cables****Rubber Cables****JFTC Unarmoured/Armoured Cables & Telephone Dry Armoured Cables****RS 485 Cables****Fire Survival Cables****FS Aluminium Cables**

"POLYCAB" Brand Power Cables, Solid Aluminum conductor up to 10 sqmm balance stranded conductor, XLPE Insulated, cores laid up, PVC tape/Extruded Innersheathed for Multicore Cables , Armour (Aluminium wire for single core up to 70 sqmm balance Aluminium strip, Galvanised wire for cables upto 2x10 sqmm, 3x10 sqmm,4x6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 sheathed, 650/1100V grade as per IS 7098(Part 1) 1988

**Aluminium Armoured**

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	1 Core	2 Core	3 Core	3.5 Core	4 Core
	A2XWaY / A2XFaY	A2XWY / A2XFY	A2XWY / A2XFY	A2XFY	A2XWY / A2XFY
2.5		226	244		269
4		244	287		319
6		306	357		400
10		354	422		553
16	245	410	469		599
25	305	423	563	661	711
35	381	542	771	854	972
50	485	732	998	1138	1281
70	616	933	1339	1551	1738
95	753	1206	1723	1964	2292
120	902	1486	2108	2462	2804
150	1074	1819	2612	2872	3388
185	1303	2221	3231	3633	4268
240	1619	2809	4180	4631	5520
300	1968	3456	5169	5743	6823
400	2541	4529	6560	7287	8773
500	3082	6289	8814	10380	11640
630	3804	7736	11204	12718	15279
800	4733				
1000	5771				

**EXTRA FOR SPECIAL CONSTRUCTION:**

a) Round Wire Armouring	
- 2 x 16 & above	30%
- 3 x 16 & 3.5CX25 & above	30%
- 4 x 10 & above	30%
- For Single core 95 & above	30%
b) Stranding 10 sq.mm and below	10%
c) Extruded PVC Innersheath Up 50	7.5%
Extruded PVC Innersheath 70 & Above	4%
d) HR PVC Insulation	17.5%
e) HR PVC Inner Sheath	7.5%
f) HR PVC Outer Sheath	7.5%
g) Oxygen Index (FR)	4%
h) PVC Insulated Cables	15%

Cable Size (Sq.mm)	FRLS Loading Factor		LSZH	
	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
	Armoured			
	Power (Al.)			
Upto 16	15%	11.5%	22.5%	30%
25 - 50	11.5%	11.5%	18%	22.5%
70 & above	7.5%	7.5%	22.5%	18%
	Power Single Core (Al.)			
Upto 16	-N.A-	15%	-N.A-	37.5%
25 - 50	-N.A-	15%	-N.A-	30%
70 & above	-N.A-	11.5%	-N.A-	26%

● The above rates are exclusive of GST which shall be charged extra.

● This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power Cables, Solid Aluminum conductor up to 10 sqmm balance stranded conductor, XLPE Insulated, cores laid up, PVC tape/Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 sheathed, 650/1100V grade as per IS 7098(Part 1) 1988

**Aluminium Unarmoured**

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	1 Core	2 Core	3 Core	3.5 Core	4 Core
	A2XY	A2XY	A2XY	A2XY	A2XY
4		136	181		218
6		196	245		278
10		267	320		386
16	139	277	372		499
25	166	345	491	629	666
35	216	464	700	757	838
50	295	608	858	1007	1105
70	401	832	1210	1392	1584
95	523	1080	1614	1842	2124
120	652	1344	2012	2334	2682
150	817	1682	2529	2823	3338
185	1001	2051	3086	3531	4108
240	1273	2620	3969	4501	5258
300	1579	3242	4914	5584	6545
400	2090	4279	6473	7142	8624
500	2589	6162	8638	10172	11407
630	3250	7581	10981	12464	14974
800	4102				
1000	5124				

**EXTRA FOR SPECIAL CONSTRUCTION:**

a) Stranding 10 sq.mm and below	10%
b) Extruded PVC Innersheath Up 50	7.5%
Extruded PVC Innersheath 70 & Above	4%
c) HR PVC Insulation	17.5%
d) HR PVC Inner Sheath	7.5%
e) HR PVC Outer Sheath	7.5%
f) Oxygen Index (FR)	4%
g) PVC Insulated Cables	15%

Cable Size (Sq.mm)	FRLS Loading Factor		LSZH	
	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
		Unarmd.		
		Power (Al.)		
Upto 16	15%	11.5%	22.5%	30%
25 - 50	11.5%	11.5%	18%	22.5%
70 & above	7.5%	7.5%	22.5%	18%
		Power Single Core (Al.)		
Upto 16	-N.A-	15%	-N.A-	37.5%
25 - 50	-N.A-	15%	-N.A-	30%
70 & above	-N.A-	11.5%	-N.A-	26%

● The above rates are exclusive of GST which shall be charged extra.

● This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power/Control Copper Cables, Solid Copper conductor upto 6sqmm balance Stranded, XLPE Insulated, cores laid up, PVC tape innersheathed for Multicore Cables, Unarmoured/Armour (Galvanised wire for cables up to 10 x 1.5 sqmm, 8 x 2.5 sqmm, 2 x 10 sqmm, 3 x 10 sqmm, 4 x 6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

**Copper Armoured**

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	4 Core	5 Core	6 Core	7 Core
	2XWaY / 2XFaY	2XWY / 2XFY	2XWY / 2XFY	2XFY	2XWY / 2XFY	2XWY / 2XFY	2XWY / 2XFY
4		499	692	900	1256	1491	1711
6		710	1002	1303	1866	2244	2617
10		1151	1639	2169	2871		
16	1001	1628	2435	3199	4277		

Control Cables (Rate in Rs. Per Mtr.)

Number of Cores	2XWY/2XFY		Number of Cores	2XWY/2XFY	
	1.5 Sq.mm.	2.5 Sq.mm.		1.5 Sq.mm.	2.5 Sq.mm.
2	257	362	14	1208	1996
3	327	481	16	1382	2256
4	411	620	19	1638	2651
5	523	770	24	2049	3339
6	631	903	27	2323	3805
7	657	1050	30	2589	4576
8	747	1211	37	3359	5344
10	936	1438	44	3923	6242
12	1053	1703	61	5776	9050

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM )	4%
C) Extruded Innersheath	4%
D) Round Wire Armouring	
1C x 95 sq. mm & above	9%
1.5 sq.mm - 12 core & above	18%
2.5 sq.mm - 9 core & above	18%
10 sq.mm - 4 core & above	18%
16 sq.mm - 2 core & above	18%
16 sq.mm - 3 core & above	18%
E) OXYGEN INDEX (FR)	4%
F) HR PVC Insulatoin	17.5%
HR I/S & O/S	7.5% Each
G) FRLS Loading-Power Cable (upto 6 Sq.mm.)	11.5%
FRLS Loading-Power Cable (10 Sq.mm. & above)	6%
H) PVC Insulated Cables	15%

FRLS Loading Factor- Control Cable			LSZH	
Cores	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
		Armoured		
2 to 4 Core	7.5%	9%	22.5%	22.5%
5 to 10 Core	7.5%	6%	22.5%	22.5%
12 & Above	7.5%	6%	18%	18%

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994,with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power/Control Copper Cables, Solid/Stranded Copper conductor, XLPE Insulated, cores laid up, PVC tape/PVC Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

**Copper Unarmoured**

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	4 Core
	2XY	2XY	2XY	2XY
4		436	636	839
6		643	945	1249
10		1090	1597	2139
16	883	1598	2405	3170

**Control Cables (Rate in Rs. Per Mtr.)**

Number of Cores	2XY		Number of Cores	2XY	
	1.5 Sq.mm.	2.5 Sq.mm.		1.5 Sq.mm.	2.5 Sq.mm.
2	195	298	14	1114	1911
3	267	420	16	1321	2176
4	350	561	19	1569	2577
5	456	702	24	1959	3254
6	547	824	27	2196	3632
7	582	976	30	2606	4305
8	670	1111	37	3374	5161
10	844	1361	44	3947	6152
12	965	1630	61	5775	8469

**EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):**

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM )	4%
C) Extruded Innersheath	4%
D OXYGEN INDEX (FR)	4%
E) HR PVC Insulation	17.5%
HR PVC I/S & O/S	7.5% Each
F) FRLS Loading-Power Cable (upto 6 Sq.mm.)	11.50%
FRLS Loading-Power Cable (10 Sq.mm. & above)	6%
G) PVC Insulated Cables	15%

FRLS Loading Factor- Control Cable			LSZH	
Cores	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
	Unarmd			
2 - 4	7.5%	9%	22.5%	22.5%
5 - 10	7.5%	6%	22.5%	22.5%
12 & Above	7.5%	6%	18%	18%

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994,with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power/Control Copper Cables, Solid Copper conductor upto 6sqmm balance Stranded, XLPE Insulated, cores laid up, PVC tape innersheathed for Multicore Cables, Unarmoured/Armour (Galvanised wire for cables up to 10 x 1.5 sqmm, 8 x 2.5 sqmm, 2 x 10 sqmm, 3 x 10 sqmm, 4 x 6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

**Copper Armoured**

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	3.5 Core	4 Core	5 Core
	2XWaY / 2XFaY	2XWY / 2XFY	2XWY / 2XFY	2XFY	2XWY / 2XFY	2XWY / 2XFY
25	1540	2535	3805	4617	5062	7809
35	2103	3743	5490	6286	7264	10763
50	2945	5053	7407	8721	9899	14799
70	4058	7506	10742	12541	14385	23274
95	5417		15041	17426	19872	
120	6790		18549	22103	24734	
150	8437		22829	26445	30609	
185	10377		28914	33800	38294	
240	13384		37712	43562	50068	
300	16669		48169	55085	63540	
400	22152		62295	69737	86779	
500	27582					
630	34675					
800	43912					
1000	54745					

POLYCAB Brand Power/Control Copper Cables, Solid/Stranded Copper conductor, XLPE Insulated, cores laid up, PVC tape/PVC Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

**Copper Unarmoured**

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	3.5 Core	4 Core	
	2XY	2XY	2XY	2XY	2XY	
25	1451	2466	3717	4522	4958	
35	2014	3661	5395	6176	7145	
50	2860	4961	7302	8603	9768	
70	3993	7389	10609	12402	14230	
95	5172		14888	17260	19698	
120	6525		18380	21907	24542	
150	8159		22656	26236	30396	
185	10055		28688	33556	38050	
240	13017					
300	16256					
400	21663					
500	27060					
630	34087					
800	43259					
1000	54054					

**EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):**

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM )	4%
C) Extruded Innersheath	4%
D) Round Wire Armouring	
1C x 95 sq. mm & above	9%
10 sq.mm - 4 core & above	18%
16 sq.mm - 2 core & above	18%
16 sq.mm - 3 core & above	18%
E) OXYGEN INDEX (FR)	4%
F) HR PVC Insulatoin	17.5%
HR I/S & O/S	7.5% Each
G) FRLS Loading-Power Cable (10 Sq.mm. & above)	6%
H) PVC Insulated Cables	15%

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994,with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Stranded Compact Circular Aluminium Conductor, Conductor Screen With Extruded Semi Conducting Compound, XLPE Insulated, Insulation Screening with extruded Semi Conducting Compound in combination with Copper Tape, cores laid up, innersheath of PVC tape, galvanised flat steel strip armoured and overall PVC Sheathed Cable conforming to IS 7098 / (PART-II) 1985 with latest amendments.

**3 Core HT Cables**

	(Rate in Rs. Per Mtr.)					
Size in Sq.mm.	3.3 KV (UE) / 6.6 KV (E)	6.6 KV (UE) / 11 KV (E)	11 KV (UE)	22 KV (E)	33 KV (E)	33 KV (UE)
35		1831				
50		2205				
70	2401	2678				
95	2851	3197	4157	4120	5265	
120	3455	3752	4502	4594	5905	
150	4051	4389	5401	5512	6875	7439
185	4777	5147	5946	6069	7573	8164
240	6114	6546	7114	7258	8717	9228
300	7022	7437	8466	8642	9968	10972
400	9067	9475	10401	10612	11940	12553

**EXTRA FOR SPECIAL CONSTRUCTION:**

1) Extruded PVC Inner Sheath	4.5%	
2) Pressure Extruded PVC Innersheath	19.5%	
3) Round Wire Armouring - Up to 11 KV (E)	30%	
11 KV (UE) & Above	33%	
4) FRLS PVC Inner Sheath	7.5%	
5) FRLS PVC Outer Sheath	7.5%	
6) FR Sheath with Oxygen Index	4.5%	

• The above rates are exclusive of GST which shall be charged extra.

• This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Stranded Compact Circular Aluminium Conductor, Conductor Screen with extruded semi conducting compound, XLPE insulated, insulation screening with extruded semi conducting compound in combination with Copper tape, AL flat strip / round armoured and overall PVC sheathed cable conforming to IS 7098 / (PART-II) 1985 with latest amendments.

**1 Core HT Cables**

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	3.3 KV (UE) / 6.6 KV (E)		6.6 KV (UE) / 11 KV (E)		11 KV (UE)		22 KV (E)		33 KV (E)		33 KV (UE)	
	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured
240	2149	2494	2250	2605	2549	2962	2630	3042	3161	3650	3620	4180
300	2541	2914	2630	2997	2945	3374	3026	3470	3592	4352	3865	4683
400	3211	3550	3262	3604	3618	4016	3712	4100	4284	5042	4532	5342
500	3851	4272	3876	4313	4256	4985	4345	5093	4954	5799	5163	6047
630	4645	5174	4661	5190	5057	5915	5154	6019	5824	6777	6063	7053
800	5651	6537	5671	6572	6105	7063	6216	7186	6914	7971	7214	8313
1000	6858	7911	6869	7911	7354	8437	7451	8572	8216	9895	8832	10678

EXTRA FOR SPECIAL CONSTRUCTION:

1) FRLS PVC Inner Sheath	11.5%
2) FRLS PVC Outer Sheath	7.5%
3) Oxygen Index	4.5%

• The above rates are exclusive of GST which shall be charged extra.

• This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

**POLYCAB Brand Aluminium Conductor, XLPE Insulated, flat strip armoured and overall PVC Sheathed Cable conforming to IS 7098(Part 1) 1988**

Sq.mm.	1.9 KV / 3.3 KV
	Armoured
1 Core x 120	683
1 Core x 150	794
1 Core x 185	976
1 Core x 240	1171
1 Core x 300	1478
1 Core x 400	1784
1 Core x 500	2371
1 Core x 630	2900

**POLYCAB Brand Sector Shaped Aluminium Conductor, XLPE Insulated, innersheath of PVC tape, Galvanised steel wire / flat strip armoured and overall PVC Sheathed Cable conforming to IS 7098(Part 1) 1988**

Sq.mm.	1.9 KV / 3.3 KV
	Armoured
3 Core x 120	1740
3 Core x 150	2133
3 Core x 185	2544
3 Core x 240	3247
3 Core x 300	3947
3 Core x 400	4917

● This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

**POLYCAB INSTRUMENTATION CABLES**

**Str/Solid Cu PVC/XLPE Insulated Core/Pair/Triad/Quad laid up together with Al (Inner sheathed GI Steel Wire Mylar/Drain Wire)  
Round/Strip Armoured PVC Outer Sheathed Instrumentation**

**OVERALL SHIELDED - ARMOURED INSTRUMENTATION CABLES**

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
CORE	2	0.5	149	0.75	172	1	193	1.5	232	2.5	357
CORE	3	0.5	176	0.75	225	1	253	1.5	329	2.5	465
CORE	4	0.5	208	0.75	265	1	307	1.5	399	2.5	607
CORE	5	0.5	278	0.75	346	1	408	1.5	521	2.5	755
CORE	6	0.5	269	0.75	356	1	429	1.5	549	2.5	872
CORE	7	0.5	340	0.75	434	1	525	1.5	682	2.5	1022
CORE	8	0.5	332	0.75	450	1	541	1.5	707	2.5	1111
CORE	10	0.5	401	0.75	563	1	665	1.5	846	2.5	1356
CORE	12	0.5	451	0.75	630	1	764	1.5	1011	2.5	1675
CORE	14	0.5	571	0.75	733	1	918	1.5	1267	2.5	1900
CORE	16	0.5	608	0.75	807	1	974	1.5	1298	2.5	2051
CORE	19	0.5	704	0.75	935	1	1186	1.5	1603	2.5	2517
CORE	24	0.5	829	0.75	1162	1	1371	1.5	1793	2.5	3176
PAIR	1	0.5	149	0.75	172	1	193	1.5	232	2.5	357
PAIR	2	0.5	226	0.75	289	1	327	1.5	425	2.5	642
PAIR	3	0.5	279	0.75	368	1	440	1.5	564	2.5	882
PAIR	4	0.5	338	0.75	460	1	553	1.5	715	2.5	1128
PAIR	5	0.5	413	0.75	570	1	674	1.5	861	2.5	1377
PAIR	6	0.5	475	0.75	656	1	793	1.5	1040	2.5	1758
PAIR	7	0.5	574	0.75	749	1	934	1.5	1281	2.5	1924
PAIR	8	0.5	609	0.75	841	1	1010	1.5	1322	2.5	2094
PAIR	10	0.5	770	0.75	1014	1	1273	1.5	1733	2.5	2657
PAIR	12	0.5	828	0.75	1176	1	1387	1.5	1907	2.5	3199
PAIR	14	0.5	960	0.75	1330	1	1680	1.5	2342	2.5	3608
PAIR	16	0.5	1094	0.75	1465	1	1899	1.5	2618	2.5	4097
PAIR	19	0.5	1245	0.75	1734	1	2210	1.5	3059	2.5	4801
PAIR	24	0.5	1553	0.75	2233	1	2910	1.5	3722	2.5	5748
TRIAD	1	0.5	184	0.75	226	1	256	1.5	348	2.5	475
TRIAD	2	0.5	321	0.75	419	1	466	1.5	604	2.5	920
TRIAD	3	0.5	463	0.75	583	1	667	1.5	875	2.5	1293
TRIAD	4	0.5	505	0.75	689	1	795	1.5	1031	2.5	1701
TRIAD	5	0.5	646	0.75	857	1	996	1.5	1347	2.5	2003
TRIAD	6	0.5	744	0.75	990	1	1171	1.5	1554	2.5	2355
TRIAD	7	0.5	824	0.75	1098	1	1306	1.5	1750	2.5	2682
TRIAD	8	0.5	879	0.75	1198	1	1354	1.5	1867	2.5	3090
TRIAD	10	0.5	1097	0.75	1498	1	1777	1.5	2446	2.5	3773
TRIAD	12	0.5	1248	0.75	1720	1	2081	1.5	2856	2.5	4464
TRIAD	14	0.5	1420	0.75	1967	1	2381	1.5	3281	2.5	5139
TRIAD	16	0.5	1574	0.75	2191	1	2677	1.5	3717	2.5	5828
TRIAD	19	0.5	1815	0.75	2547	1	3116	1.5	4342	2.5	6834
TRIAD	24	0.5	2247	0.75	3187	1	3894	1.5	5467	2.5	8599
QUAD	1	0.5	215	0.75	279	1	315	1.5	414	2.5	623

**POLYCAB INSTRUMENTATION CABLES**

**Str/Solid Cu PVC/XLPE Insulated Pair/Triad laid up together with Al Mylar/Drain Wire Inner sheathed, GI Steel Wire Round/Strip Armoured PVC Outer Sheathed Instrumentation Cables**

**INDIVIDUAL & OVERALL SHIELDED - ARMoured INSTRUMENTATION CABLES**

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
PAIR	2	0.5	369	0.75	414	1	405	1.5	487	2.5	789
PAIR	3	0.5	474	0.75	528	1	623	1.5	763	2.5	1076
PAIR	4	0.5	568	0.75	650	1	756	1.5	958	2.5	1326
PAIR	5	0.5	669	0.75	769	1	912	1.5	1121	2.5	1618
PAIR	6	0.5	738	0.75	892	1	974	1.5	1232	2.5	1884
PAIR	7	0.5	844	0.75	987	1	1177	1.5	1487	2.5	2144
PAIR	8	0.5	960	0.75	1091	1	1317	1.5	1686	2.5	2446
PAIR	10	0.5	1132	0.75	1332	1	1604	1.5	2061	2.5	3000
PAIR	12	0.5	1265	0.75	1550	1	1735	1.5	2271	2.5	3433
PAIR	14	0.5	1464	0.75	1743	1	2126	1.5	2747	2.5	4061
PAIR	16	0.5	1647	0.75	1961	1	2384	1.5	3096	2.5	4594
PAIR	19	0.5	1881	0.75	2256	1	2757	1.5	3616	2.5	5371
PAIR	24	0.5	2341	0.75	2835	1	3465	1.5	4560	2.5	6757
TRIAD	2	0.5	457	0.75	525	1	595	1.5	738	2.5	1019
TRIAD	3	0.5	568	0.75	669	1	776	1.5	983	2.5	1392
TRIAD	4	0.5	693	0.75	831	1	962	1.5	1207	2.5	1766
TRIAD	5	0.5	821	0.75	990	1	1164	1.5	1486	2.5	2190
TRIAD	6	0.5	947	0.75	1132	1	1336	1.5	1740	2.5	2571
TRIAD	7	0.5	1048	0.75	1263	1	1499	1.5	1970	2.5	2921
TRIAD	8	0.5	1172	0.75	1451	1	1704	1.5	2247	2.5	3332
TRIAD	10	0.5	1411	0.75	1756	1	2087	1.5	2758	2.5	4142
TRIAD	12	0.5	1633	0.75	2037	1	2436	1.5	3223	2.5	4855
TRIAD	14	0.5	1835	0.75	2316	1	2798	1.5	3718	2.5	5593
TRIAD	16	0.5	2065	0.75	2611	1	3141	1.5	4206	2.5	6348
TRIAD	19	0.5	2392	0.75	3035	1	3687	1.5	4945	2.5	7435
TRIAD	24	0.5	3000	0.75	3820	1	4647	1.5	6179	2.5	9412

**ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED ELASTOMERIC SHEATHED CABLES (Rate Per Mtr)**

Size	1.5 Sq.mm.	2.5 Sq.mm.	4 Sq.mm.	6 Sq.mm.	10 Sq.mm.	16 Sq.mm.	25 Sq.mm.	35 Sq.mm.	50 Sq.mm.
1 Core						825	1213	1687	2416
2 Core	185	297	450	680	1161	1821	2775	3735	5314
3 Core	258	425	649	979	1682	2581	3984	5497	7854
4 Core	347	559	851	1291	2207	3407	5230	7228	10392
5 Core	455	763	1169						
6 Core	516	835							
7 Core	582	951							
8 Core	668	1142							
10 Core	851	1419							
12 Core	1002	1676							
14 Core	1161	1944							
16 Core	1317	2211							
19 Core	1597	2597							
24 Core	2034	3298							

**ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED ELASTOMERIC SHEATHED CABLES (Rate Per Mtr)**

Size	70 Sq.mm.	95 Sq.mm.	120 Sq.mm.	150 Sq.mm.	185 Sq.mm.	240 Sq.mm.	300 Sq.mm.	400 Sq.mm.	
1 Core	3411	4485	5700	7102	8669	11452	14359	18885	
3 Core	11085	14577	18526	23081	28244	37050	47073	60738	
4 Core	14638	19436	24295	30370	37111	48894	61118	80478	

**POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED, UNARMoured POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION**

Rate/Mtr.

SIZE	5 PAIR	10 PAIR				
0.5	168	261				

**POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED, G.S.TAPE ARMoured POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION**

Rate/Mtr.

SIZE	5 PAIR	10 PAIR	20 PAIR	50 PAIR	100 PAIR	200 PAIR
0.5	220	338	596	1319	2517	4620

**POLYCAB BRAND SOLID COPPER CONDUCTOR, POLYTHENE INSULATION, TWISTED PAIRS, LAY-UP, EXTRUDED ST1 GREY PVC INNER SHEATH, SINGLE LAYER GS ROUND WIRE ARMoured, EXT ST1 GREY PVC OUTER SHEATHED TELEPHONE ARMoured CABLE AS PER BSNL GR/WIR-06/03 MAR 2002**

SIZE	5 PAIR	10 PAIR	20 PAIR			
0.5	192	368	570			

**POLYCAB RS 485 CABLES (Armoured)**

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm<sup>2</sup> ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / Extr. PVC ST1/ Armoured/ PVC ST1 sheathed Cable

Pairs	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	206
	22 AWG	0.32	233
	20 AWG	0.50	250
	18 AWG	0.80	300
	17 AWG	1.00	333
2 Pair	24 AWG	0.205	309
	22 AWG	0.32	341
	20 AWG	0.50	356
	18 AWG	0.80	488
	17 AWG	1.00	547

**POLYCAB RS 485 CABLES (Un Armoured)**

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm<sup>2</sup> ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / UnArmoured/ PVC ST1 sheathed Cable

Size	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	138
	22 AWG	0.32	159
	20 AWG	0.50	176
	18 AWG	0.80	227
	17 AWG	1.00	255
2 Pair	24 AWG	0.205	214
	22 AWG	0.32	255
	20 AWG	0.50	288
	18 AWG	0.80	385
	17 AWG	1.00	441

**POLYCAB RS 485 CABLES (Armoured)**

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm<sup>2</sup> ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / LSZH Extr. PVC ST1/ Armoured/ LSZH sheathed Cable

Pairs	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	231
	22 AWG	0.32	261
	20 AWG	0.50	280
	18 AWG	0.80	336
	17 AWG	1.00	373
2 Pair	24 AWG	0.205	346
	22 AWG	0.32	382
	20 AWG	0.50	399
	18 AWG	0.80	547
	17 AWG	1.00	613

**POLYCAB RS 485 CABLES (Un Armoured)**

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm<sup>2</sup> ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / UnArmoured/ LSZH sheathed Cable

Size	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	155
	22 AWG	0.32	178
	20 AWG	0.50	197
	18 AWG	0.80	254
	17 AWG	1.00	286
2 Pair	24 AWG	0.205	240
	22 AWG	0.32	286
	20 AWG	0.50	323
	18 AWG	0.80	431
	17 AWG	1.00	494

**Fire Survival Cables**

**Stranded Annealed Bare Copper Conductor /95° Mica Tape Wrapped/Xlpe Insulation/Cores Laid up together/FRLS Inner Sheathed/GI Wire Strip Armoured/ FRLS Outersheathed Fire Survival Cables**

Rate/Mtr.				
Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	375	431		544
2.5	498	677		765
4	672	876		957
6	840	1216		1440
10	1241	1836		2166
16	1746	2672		3300
25	2520	3871	4398	4839
35	3420	5281	6000	6651
50	4695	6936	7801	8970
70	6450	9973	10951	13051
95	8881	13651	14851	17551
120	13801	17266	18902	22201

**Fire Survival Cables**

**Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Xlpe Insulation/Cores Laid up together/Zero Halogen Inner Sheathed/GI Wire Strip Armoured/ Zero Halogen Outersheathed Fire Survival Cables**

Rate/Mtr.				
Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	418	476		595
2.5	549	733		821
4	733	939		1017
6	899	1288		1515
10	1312	1918		2251
16	1821	2758		3407
25	2614	3981	4517	4962
35	3524	5407	6134	6792
50	4816	7072	7945	9136
70	6596	10153	11136	13259
95	9062	13850	15059	17787
120	14035	17490	19152	22486

**Fire Survival Cables**

**Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Cross Linkable Zero Halogen Insulation/Cores Laid up together/Zero Halogen Inner Sheathed/GI Wire Strip Armoured/ Zero Halogen Outsheathed Fire Survival Cables**

Rate/Mtr.				
Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	434	499		622
2.5	568	763		855
4	757	969		1057
6	922	1327		1565
10	1341	1966		2312
16	1856	2822		3481
25	2673	4076	4630	5081
35	3593	5513	6263	6931
50	4908	7213	8108	9318
70	6717	10343	11349	13510
95	9194	14066	15307	18061
120	14241	17756	19454	22831

**FS Aluminium Power Cables**

**Polycab Make Stranded Sector Aluminium Conductor/Wrapped with Mica Tape/Xlpe Insulation/FRLS Inner Sheathed/GI Wire Strip Armoured/FRLS Sheathed FS Aluminium Power Cables**

<b>Sq.mm.</b>	<b>3 Core</b>	<b>4 Core</b>
<b>16</b>	<b>591</b>	<b>755</b>
<b>25</b>	<b>816</b>	<b>1028</b>
<b>35</b>	<b>1004</b>	<b>1279</b>
<b>50</b>	<b>1251</b>	<b>1622</b>
<b>70</b>	<b>1670</b>	<b>2172</b>
<b>95</b>	<b>2058</b>	<b>2660</b>
<b>120</b>	<b>2481</b>	<b>3246</b>
<b>150</b>	<b>2985</b>	<b>3881</b>
<b>185</b>	<b>3645</b>	<b>4740</b>
<b>240</b>	<b>4606</b>	<b>5998</b>
<b>300</b>	<b>5588</b>	<b>7309</b>
<b>400</b>	<b>7025</b>	<b>9175</b>