

UR ∋)

Control and Signaling Devices Ø 30.5 Series


MRP with effect from 10.07.2023















SALIENT FEATURES

The Ø30.5 range of pushbuttons, selector actuators, pilot lights and illuminated pushbuttons have been designed to provide the following salient features:

- · Aesthetically elegant
- Easy and rapid mounting
- Dust, moisture and oil tight
- Robust in material of construction
- SELF WIPING CONTACTS
- Safe in operation
- Long mechanical and electrical life

The control devices are designed for flush mounting on control panels, desks and machines with plate thickness upto 6mm. Their dust, moisture and oil tight construction make them specially suitable for application in power plants, steel plants, cement plants, coal handling plants, foundries machine tools etc. Booted pushbuttons are used in very dusty atmospheres.

The pushbuttons comprises of the actuators and contact element. The actuator is designed to contain a full umbrella type of special rubber diaphragm inside the actuator housing in order to provide dust, moisture and oil tight onstruction. The different types of actuators include shrouded, unshrouded booted, mushroom spring return or stayput, mushroom jumbo, selector, key, luminous. Different versions including dust proofing version are described in detail in TEKNIC price list.

The contact element comprises of a contact housing, fixed and moving silver tipped contacts, a slider ans a transparent cover through which the contacts can be inspected in operation. Contacts are double break are **self wiping** which ensures long life. Each contact element provides 1NO and 1NC contact. Each unit can take upto 4 contact elements. Separate contact elements can be used on different phases or polarities.

The pilot lights and illuminated pushbuttons are suitable for direct supply or supply through series resistor, using bayonet cap filament bulb.

The pilot light can also be provided with neon bulbs. Replacement of the bulb is easily done by unscrewing the front ring, holding the lense. Pilot lights can be provided with either glass or polycarbonate lenses in the following standard colours

TRANSLUCENT WHITE

GREEN

RED

AMBER

BLUE

CLEAR

Supply voltage for direct connection or without series resistor: 6V-230V Supply voltage for direct connection with series resistor : 24V-230V Pilot lights can also be supplied with neon bulbs upto a voltage of 500V

FIXING

The control devices Ø30.5 can be fixed in any position on panel of 1 to 6mm thickness. They are secured from the front by means of a fixing ring. A set of rubber gaskets is supplied to provide water proofing and tightness between the unit and the panel. The exact number of rubber gaskets is to be selected depending upon the panel thickness. Fixing centres of 60mm are recommended between control stations to provide sufficient space for convenient terminal connections and assembly of legend plates.

The pushbutton can be either be mounted as complete unit on the front of the panel or the contact can be individually mounted with the actuator on the panel front plate. Also the pilot light can either be mounted as a complete unit on the front of the panel or the pilot light holder can be individually mounted with the lense on the front of the panel.

ELECTRICAL AND MECHANICAL CHARACTERISTICS

Rated insulation voltage : 500V AC, 600V DC

Rated thermal current : 10A

Contact operation : Self wiping, slow double break, 1 NO + 1 NC

Make and break capacity (13947-5-1) : AC15: 4A 415V

: DC13: 0.5A 110V
Terminal capacity : Maximum 2x1.5mm²
: Minimum 1X0.5mm²

Ambient temperature : -25°C to +70°C
Altitude : < 3000 metres
Operating position : All positions

Degree of protection : IP 65

Mechanical life : Over 1 million operations

ORDERING INSTRUCTIONS

- 1. Actutors, illuminated actuators, contact elements, pilot lights can be ordered separately or in combination.
- 2. No prefix before all actuators and combinations indicates Ø30.5 series
- 3. Numerical colour code has been added as suffix to indicate colour of the actuator or lense as follows:

Colour of Actuator: White Black Green Red Yellow Blue Colour of Lense: Translucent white Green Red Amber Blue Clear Colour code: 1 2 3 4 5 6 7

4. The type number of contact elements are S11, S12, S21, S22. All these have 1NO+1NC contacts. S11 is for mounting directly to actuator and S12 for coupling to S11 for obtaining 2NO+2NC. S21 is for individual mounting and S22 is for coupling for S21 for 2NO+2NC

BULBS

Filament Bulbs type BA15d

Voltage: 6 12 24 48 110 220 Wattage (max) 5-7 5-7 5-7 5-7 5-7

LEGEND PLATES

Legend plates are supplied with the following standards texts

AUTO RESET START **FORWARD** UP ON **OPEN SLOW STOP** REVERSE **DOWN OFF CLOSE HAND FAST INCH**

TYPE NUMBERS

Some examples of type number

Actuator Type AF3 means type actuator Ø30.5 GREEN
Pilot Light Type PLB4 means pilot light without resistor RED

Type PLBR3 means pilot light with series resistor GREEN

Complete Pushbutton Type PSF411 means flush type pushbutton RED with 1NO+1NC

1NO+1NC Element (S11)
Colour of Actuator Red
Ø30.5 Flush type pushbutton



ТҮРЕ	COLOUR	ORDERING CODE	PRICE IN Rs
	White	AF1	135.00
<u> </u>	Black	AF2	135.00
Flush Momentary	Green	AF3	135.00
riadii ilidaii y	Red	AF4	135.00
	Blue	AF6	135.00
	Yellow	AF8	135.00
	White	AP1	135.00
	Black	AP2	135.00
Projecting Momentary	Green	AP3	135.00
	Red	AP4	135.00
	Blue	AP6	135.00
	Yellow	AP8	135.00
	Black	AB2	240.00
	Green	AB2 AB3	240.00
Booted Momentary	Red	AB4	240.00
booted Momentary	Blue	AB6	240.00
	Yellow	AB8	240.00
Mushroom Momentary	Black	AM2	150.00
Head Ø 40mm	Red	AM4	150.00
Jumbo Mushroom	Black	AMJ2	240.00
Momentary Head Ø 60mm	Red	AMJ4	240.00



	ACTUATOR	2010115					
	ТҮРЕ	COLOUR	ORDERING CODE	PRICE IN Rs.			
	MUSHROOM HEAD	MUSHROOM HEAD ACTUATOR					
	Mushroom	Black	AML2	220.00			
	Latching	Red	AML4	220.00			
	Head Ø 40mm						
3	Jumbo Mushroom	Black	AMLJ2	310.00			
	Latching	Red	AMLJ4	310.00			
	Head Ø 60mm	1100	7				
	Key Mushroom						
	Latching	Red	AMLKB4	425.00			
	Head Ø 40mm						
	SELECTOR ACTUAT	OR					
	2 Position						
	STAY PUT	Black	AS2-2P	275.00			
	2 Position						
	MOMENTARY	Black	AS2-2PSR	275.00			
	Q. C.						
	3 Position						
	STAY PUT	Black	AS2-3P	275.00			
	0,00						



MRP w.e.f. 10.07.2023

Control & Signalling Devices 30.5 Ø

	ТҮРЕ	COLOUR	COLOUR	ORDERING CODE	PRICE IN Rs.			
	KEY SELECTOR	KEY SELECTOR						
		ă,ă	Black	AK-2PB	410.00			
	2 Position Stayput	مُرِهُ		AK-2PO	410.00			
		a ×		AK-2PI	410.00			
	Spring Return	۵۰۰۰۰		AK-2POSR	410.00			
		ă Š ŏ		AK-3PA	430.00			
		à o ò	Black	AK-3PB	430.00			
	3 Position Stayput	à g o		АК-ЗРО	430.00			
		٩٩٥		AK-3PI	430.00			



LEGIVIIIVATED FEOSI	I ACTUATOR WITH LED B			PRICE IN Rs.	PRICE IN Rs.			
	ТҮРЕ	COLOUR	ORDERING CODE	INTEGRAL LED	WITH LED BULB			
	Illuminated Flush Act	uator, Spring Return						
14.10	LED Bulb, MCB15 type	White LED Bulb / White Lens	ALF1LB(S)		630.00			
	24V AC/DC,	Green LED Bulb / Green Lens	ALF3LB		365.00			
	110VAC, 110VDC	Red LED Bulb / Red Lens	ALF4LB		365.00			
	230VAC, 220VDC	Amber LED Bulb / Amber Lens	ALF5LB		365.00			
		Blue LED Bulb / Blue Lens	ALF6LB		660.00			
		White LED Bulb/ Clear Lens	ALF7LB(S)		630.00			
		Yellow LED Bulb / Yellow Lens	ALF8LB		365.00			
LED Bulb		Please mention the voltage required after the ordering code						
	PILOT LIGHT	•			•			
			21 22 41 (2)					
	Integral LED	White LED / White Lens	PLBR1L(S)	430.00				
	6V, 12V, 24V, 48V AC/DC	Green LED / Green Lens	PLBR3L	290.00	_			
NAME TO THE CASE OF THE STATE O	110VAC, 110VDC,	Red LED / Red Lens	PLBR4L	290.00				
UED SZ BART AS 8 2014 C 6	230VAC, 220VDC	Amber LED / Amber Lens	PLBR5L	290.00	<u> </u>			
		Blue LED / Blue Lens	PLBR6L	575.00				
		White LED / Clear Lens	PLBR7L(S)	430.00				
		Yellow LED / Yellow Lens	PLBR8L	290.00				
Integral LED	Please mention the voltage requ	ired after the ordering code			l .			
		White LED Bulb / White Lens	PLB1LB(S)		560.00			
	LED Bulb, MCB15 type	Green LED Bulb / Green Lens	PLB3LB		310.00			
	24V AC/DC,	Red LED Bulb / Red Lens	PLB4LB		310.00			
Jan 3	110VAC, 110VDC	Amber LED Bulb / Amber Lens	PLB5LB		310.00			
	230VAC, 220VDC	Blue LED Bulb / Blue Lens	PLB6LB		590.00			
		White LED Bulb/ Clear Lens	PLB7LB(S)		560.00			
		Yellow LED Bulb / Yellow Lens	PLB8LB		310.00			
		<u> </u>			<u> </u>			
LED Bulb	Please mention the voltage requ	ired after the ordering code						



CONTACT ELEMENTS					
	ТҮРЕ	ORDERING CODE	PRICE IN Rs.		
S11 S12	ACTUATOR MOUNTING				
	1NO+1NC	S11	250.00		
S11+S12	1NO+1NC coupled to S11 to provide 2NO+2NC	S12	250.00		
	BASE MOUNTING				
S21 S22					
	1NO+1NC	S21	250.00		
521 + 522	1NO+1NC coupled to S21 to provide 2NO+2NC	S22	250.00		

Control and signalling devices Ø30.5

Description	Type of Actuator	Type of Actuator or Lense	Colour of Element S11 (1NO + 1NC)	Type of Complete Control Device	
Flush Pushbutton	AF3	Green	1NO + 1NC	PSF311	
	AF8	Yellow	2NO + 2NC	PSF822	1 60 11.5
Projecting Pushbutton	AP2	Black	1NO + 1NC	PSP211	<u> </u>
	AP4	Red	3NO + 3NC	PSP433	
Booted Pushbutton	AB3	Green	1NO + 1NC	PSB311	
	AB4	Red	2NO + 2NC	PSB422	1 <u>9</u>
Mushroom Pushbutton (Spring return)	AM2	Black	1NO + 1NC	PSM211	£ 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
Mushroom Jumbo Pushbutton (Spring return)	AMJ4	Red	4NO + 4NC	PSMJ444	
Mushroom Pushbutton Latching. Turn to	AML2	Black	1NO + 1NC	PSML211	₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽₽
Release.	AML4	Red	2NO + 2NC	PSML422	
Mushroom Pushbutton Latching. Key to Release.	AMLKB4	Red	1NO + 1NC	PSMLKB411	
Selector Actuator (2 Pos.)	AS2-2P	Black	1NO + 1NC	PSS211-2P	
Selector Actuator (3 Pos.)	AS2-3P	Black	2NO + 2NC	PSS222-3P	132
Key Actuator (2 Pos.)	AK2-2P		1NO + 1NC	PSK211-2P	
Key Actuator (3 Pos.)	AK2-3P		2NO + 2NC	PSK222-3P	3111
Pilot Light for direct connection upto 230\	V (LED Bulk	Red		PLB4LB (240V AC)	<u>55</u>
Pilot Light through series resistor for 230V (LED E	s `	Green		PLBR3LB (240V AC)	10 26 26
Illuminated Pushbutton direct connection upto 230V	AL5LB (LED Bulb)	Amber	1NO + 1NC	PSL5LB11 (230V)	· — · — ·
					40



GENERAL TERMS AND CONDITIONS

General Terms : Prices are ex-works Mumbai

HSN CODE : 85365010 for all the products of this MRP List

GST : 18%

Prices are subject to revision without notice and ruling at the time of delivery.

This price list supersedes all previous Price Lists.

Warranty Policy: TEKNIC equipment is guaranteed under the following terms:

For a period of 12 months from the date of sale, TEKNIC guarantees that its products are free from defects in material and workmanship, with the exception of consumables rendered unserviceable through normal use. During the said period, TEKNIC will replace or repair all parts acknowledged as defective due to factory workmanship and which have been returned in a timely manner by Buyer to TEKNIC and all costs and duties paid, together with a detailed description of the failure and a certified declaration of the number of hours of operation. Repaired or replaced parts will be redelivered FCA (named place) as per INCOTERMS 2000. This warranty is subject to the provision of correct usage, proper maintenance and does not cover defects arising out of fire, faulty operation, accident, inefficient maintenance and willful or accidental damage.

TEKNIC guarantee applies to all equipment, parts and components stored, installed, protected, maintained and used in accordance with TEKNIC specifications and instructions, and respecting the rules for normal use, without any modification by Buyer.

All other conditions or warranties, whether express or implied, relating to the quality and operation of the equipment are excluded, as well as any liability for loss or damage caused directly or indirectly by the equipment or resulting from its use.

Proof of purchase to be provided to avail warranty.

TEKNIC ELECTRIC (I) PVT. LTD.

Reg.Office : 116, Hammersmith Industrial Estate, Mahim (W), Mumbai – 400016.

Head Office : 703/704/705, Madhava, Bandra Kurla Complex, Bandra (E), Mumbai – 400051. Tel: +91-22-42532500

Works: 65, Marol Co-op. Industrial Estate Ltd., M. Vassanji Road, Andheri (East), Mumbai – 400059. Tel: +91-22-42534500

Email : teknic@teknic.co.in mfg@teknic.co.in Website : www.teknic.co.in