

PRINTED SOFT TUBING/ FERRULE SLEEVES

..(6)

STD WALL THICKNESS : 0.40MM

SR	ID/MM	SUITABLE WIRE SIZE	LENGTH/MTRS	RATE/COIL
1	2.2	0.25 SQMM	100 MTRS	356
2	2.5	0.25 SQMM	100 MTRS	412
3	3	0.50 SQMM	100 MTRS	469
4	3.2	0.75 SQMM	100 MTRS	525
5	3.5	1.00 SQMM	100 MTRS	562
6	3.7	1.50 SQMM	100 MTRS	600
7	4	2.50 SQMM	100 MTRS	637
8	4.2	2.50 SQMM	100 MTRS	694
9	4.5	2.50 SQMM	100 MTRS	768
10	5	4.00 SQMM	100 MTRS	806
11	5.2	4.00 SQMM	100 MTRS	862
12	5.5	4.00 SQMM	100 MTRS	937
13	6	6.00 SQMM	100 MTRS	1070
14	6.2	6.00 SQMM	100 MTRS	1125
15	7	10.00 SQMM	30 MTRS	1368
16	8	16.00 SQMM	30 MTRS	1504
17	9	16.00 SQMM	30 MTRS	N/A
18	10	25.00 SQMM	30 MTRS	960
19	12	35.00 SQMM	30 MTRS	1265

**SPIRAL WIRE BIND**

..(6)

MATERIAL : LDPE

OPERATING TEMP: -5 C to 80 C

WHITE RATE	SIZE	BLACK RATE	ID/MM	OD/MM	LENGTH
175	3/4MM	185	3/4.	6	50
195	6MM	205	6	8	50
200	9/10MM	210	7.5	10	25
335	12MM	351	9	12	25
575	16MM	604	12	15	25
800	19MM	840	15	19	25
1200	25MM	1260	20	24	25

