

# PVC HEAT SHRINKABLE SLEEVES

<b>Busbar Properties</b>	
<b>Working Temp</b>	90° C (120° On Request)
<b>Dielectric Strength</b>	20 KV/mm
<b>Insulation Resistance</b>	20 x 10 Ohms at 500 Vdc
<b>Tensile Strength</b>	Mnn 400 Kg/cm <sup>2</sup>
<b>Ultimate Elongation</b>	Min 11%
<b>Chemical Resistance</b>	Goods
<b>Fire Resistance</b>	Self Extinguishing with no Dripping Of Materials
<b>Shrinking Temperature</b>	150°C - 170°C For 4-5 Minutes
<b>Heat Dissipation</b>	Excellent
<b>Mechanical Strength</b>	Excellent

6	WEF: 05-03-2021		
SR	BUSBAR SIZE (SIZE IN MM)	SUITABLE SIZE OF SLEEVES (W)	RATE/MTR
1	6 x 4	15mm	7.5
2	8 x 4 ; 6 x 6 ; 10 x 3	17mm	7.5
3	12 x 3 ; 9 x 6	20mm	8.5
4	15 x 3 ; 12 x 6	25mm	8.75
5	20 x 3 ; 18 x 6 ; 16 x 3	30mm	9.1
6	25 x 3 ; 20 x 6	35mm	10.25
7	25 x 6 ; 25 x 9	41mm	11.5
8	30 x 10 ; 30 x 6 ; 25 x 12	48mm	13.75
9	38 x 6 ; 30 x 12	55mm	15.25
10	40 x 10 ; 40 x 6 ; 38 x 12 ; 38 x 9	61mm	16.5
11	50 x 6	73mm	20.5
12	50 x 12 ; 50 x 10	81mm	23
13	60 x 10 ; 60 x 12	85mm	23.5
14	75 x 6	93mm	25
15	75 x 12	103mm	29.5
16	90 x 12 ; 90 x 6	110mm	33
17	100 x 9 ; 100 x 6	128mm	36
18	100 x 12	140mm	43
19	120 x 6 ; 120 x 10 ; 125 x 6	150mm	47
20	125 x 10 ; 125 x 6	170mm	50
21	150 x 12 ; 150 x 10 ; 150 x 6	190mm	57.75
22	175 x 12 ; 175 x 10 ; 150 x 12	210mm	65.75
23	200 x 6	230mm	72.75
24	200 x 12	250mm	83.25
25	250 x 6 ; 250 x 12	300mm	107



[www.sme.supply](http://www.sme.supply)

Email : [sme@sme.supply](mailto:sme@sme.supply)

+91 98677 61322

 **SME**.supply