KAYCEE

KI

KAYCEE
Brand that set the standards

TIME TOTALIZER

Tells how long electronic gear operates, electric machinery has run, components are in operation or maintenance checks are due

KAYCEE

HOURS
TYPE - TT 5 / Hz
230 / 240V~ 50 Hz

APPLICATIONS

- Air Compressors
- Circuit Breakers
- Generators
- Computers
- Radio and TV Stations
- Machine Tools
- Textile Machines
- Air Conditioners
- Boilers
- Power Plants
- Elevators
- Mouldings Machines
- Electric Furnaces
- Laboratories

In any other machine, process or equipment where AC power used.

In many industries, it is important to know the length of time a machine or equipment has been used. The purpose is to cut down production cost by checking the operating hours of machines.

Kaycee Time Totalizers tell you when Lubrication, Overhaul, Adjustment or Replacement of component is due on Machine Tools, Industrial Machinery, and Test Equipment or complete Processing Systems.

Kaycee Time Totalizer incorporates a self-starting synchronous movement ensuring accurate summation of ON TIME of any circuit fed from an AC Supply. Each time the machine is switched on, the Totalizer records the running time of that machine directly on the straight reading dial to read either in hours or minutes down to tenths.

All models of Time Totalizer are suitable for flush panel mounting.

TESTED AT ERTL FOR VIBRATION TEST
AND NORTH LAB CALIBRATION

KAYCEE

KAYCEE

HOURS 3/10
TYPE - TT6/H
230/240V~50 Hz
MADE IN INDIA

Ø 55

88

Hex. Nut
(8-Nos.)

Spring Washer
(8-Nos.)

11   53

88

Hex. Bolt (4-Nos.) M4 X 20 Lg.
Equally Spaced at 91 P.C.D.

90°

Hole, Ø 61

4 - Hole, Ø 4.5 Equally
Spaced at 91 P.C.D.

PANEL DRILLING

ALL DIMENSIONS ARE IN MM

ELECTRICAL DATA

Voltage Proof Test	: 1.5 KV (R.M.S.)
Ambient Temperature	: 20^0 C to 50^0 C
Power Consumption	: 2.5 Watts approx

MECHANICAL DATA

|	
Operating Voltage	: 230 - 240 Volts AC
Frequency	: 50 Hz
Face Size	: 90 mm x 90 mm approx.
Weight	: 180 gms approx.
Counting Range	: Given in the table
Mounting	: Flush Panel
Height of Figures	: 3.5 mm

The Product development being a continuous process in KAYCEE, the product supplied may differ from the illustrated & described in the literature.

CONNECTIONS
(Any one phase and neutral)

Single Phase

or three phase
AC Supply

Starter
Switch

Neutral

Equipment
or Motor

T T

Single or three phase supply.

TT6-H	TT5-H	TT5-HZ
99999.9	9999.9	9999.9

KAYCEE
### Brand that set the standards

DIGITAL TIME TOTALIZER

Tells how long the machine, electronic gear operates, electric machinery has run, components are in operation or maintenance checks are due In many industries, it is important to know the length of time a machine or equipment has been used. The purpose is to cut down production cost by checking the operating hours of machines.

Kaycee Digital Time Totalizers tell you when Lubrication, Overhaul, Adjustment or Replacement of component is due on Machine Tools, Industrial Machinery and Test Equipment or complete Processing Systems.

Kaycee Digital Time Totalizer incorporates a self-starting does not required any external auxiliary power supply for both AC/DC modules. Each time the machine is switched on, the Totalizer records the running time of that machine directly which will reflect on Display to read either in Hours / Minutes or Minutes/seconds.

All models of Time Totalizer are suitable for flush panel mounting.

APPLICATIONS
- Air Compressors
- Circuit Breakers
- Generators
- Computers
- Radio and TV Stations
- Machine Tools
- Textile Machines
- Air Conditioners
- Boilers
- Power Plants
- Elevators
- Mouldings Machines
- Electric Furnaces
- Laboratories

**WITHOUT RESET, WITH RESET,
6 DIGITS (HHHH:MM OR MMMM:SS)**

TECHNICAL DATA
Operating Voltage : 230V AC (+ 5%, -15%)
Frequency : 50 Hz
VA Burden : 7.8va @ 230V AC
  or 7.8x 0.95 = 7.41W

Considering power factor as 0.95
Display : 8mm RED seven segment.
Display Mode : HHHH.MM
  MMMM.SS
Reset : Available
Timing function : Microcontroller base crystal
  controller timer
Accuracy : +/- 5 sec per 24 hrs.
Temprature category: up to 50°C
Cut out size : 90mm x 90 mm
Mounting : Flush Panel.

The Product development being a continuous process in KAYCEE, the product supplied may differ from the illustrated & described in the literature.

HEX.NUT(8-Nos.)
SPRING WASHER(8-Nos.)
11   53
HEX.BOLTS (4-NOS.) M4x20Lg.
EQUALLY SPACED AT 91 P.C.D.

88

HOLE Ø74
4-HOLES Ø4.5 EQUALLY SPACED AT 91 P.C.D.
PANEL DRILLING

ALL DIMENSIONS ARE IN MM

CONNECTIONS
(Any one phase and neutral)
Starter Switch
Single Phase   Neutral   Equipment or Motor
or three phase AC Supply
T T
Single or three phase supply.

Manufactured by :
KAYCEE INDUSTRIES LIMITED
32, Ramjibhai Kamani Road, Ballard Estate,
Mumbai - 400 001
Tel.: 91-22-22613521 / 22 / 23 / 22616106
Email : sales@kayceeindustries.com
Website : www.kayceeindustries.com