

ANCHOR[®] HEAVY DUTY GREY SUCTION



TUBE:

- Strong, Flexible & Smooth Plasticized PVC.

REINFORCEMENT:

- Shock Resistant Hard Rigid PVC Spiral.

TEMP RANGE:

- -10°C to + 70°C Approx

APPLICATIONS:

- Coal, Mineral Mines, Stone & Lime Quarries.
- Shipping & Sewage Disposal De-Watering.
- Paper Mills, Cement Conveying Industries, Petrochemicals & Oil Exploration.
- Fire Fighting Equipments, Constructional Engineering.
- Metro Railway Projects.

FEATURES:

- Excellent Resistance in high pressure.
- Minimum Friction Loss, Saves Energy & High Flow Rate.
- Smooth Inside Surface Results in Quick Conveyance of Fluids.
- Abrasion Resistant

SIZE (MM)	SIZE (INCH)	I.D (MM)	O.D (MM)	THICKNESS (MM)	APP WT MTR (KG)	BENDING RADIUS (MM)	WORKING PRESSURE (BAR)	LENGTH PER ROLL (MTR)	RATE PER MTR (INR)
20	3/4"	19	25	3	0.30	45	8	30	80/-
25	1"	25	32	3.5	0.40	60	7	30	100/-
30	1 1/4"	31	38	3.5	0.50	80	7	30	128/-
40	1 1/2"	38	45	3.5	0.60	110	4.5	30	170/-
50	2"	50	58	4	1.00	130	4.5	30	255/-
65	2 1/2"	63	73	5	1.35	175	4.5	30	335/-
75	3"	75	86	5.5	1.65	275	4.5	30	416/-
100	4"	101	116	7.5	3.00	240	4	30	740/-
125	5"	126	142	8	4.00	280	3	15	1070/-
150	6"	152	173	10.5	6.00	400	2.5	15	1380/-
200	8"	203	224	10.5	10.00	600	2.5	6	2550/-