

ANCHOR[®] MEDIUM DUTY SUCTION HOSE (GREEN)



TUBE:

- Strong, Flexible & Smooth Plasticized PVC.

REINFORCEMENT:

- Shock Resistant Hard Rigid PVC Spiral.

TEMP RANGE:

- -5°C to + 70°C Approx

APPLICATIONS:

- Suction & Delivery Of Water For Irrigation Purpose Agricultural With Electro Mono Block & Oil Engines.
- Suction & Delivery of Saline Water, Light Acids, Alkalies & Other Chemicals Except Solvents.
- For Conveying of Granules or Fine Particles of Raw Materials in Processing Industries.

FEATURES:

- Long Retained flexibility
- Bending Radius Very Good.
- No Kinking, Bulging Or Bursting Even In The Most Severe Working Conditions.

| SIZE (MM) | SIZE (INCH) | I.D (MM) | O.D (MM) | THICKNESS (MM) | APP WT MTR (KG) | BENDING RADIUS (MM) | WORKING PRESSURE (BAR) | LENGTH PER ROLL (MTR) | RATE PER MTR (INR) |
|-----------|-------------|----------|----------|----------------|-----------------|---------------------|------------------------|-----------------------|--------------------|
| 20 | 3/4" | 19 | 23 | 2 | 0.23 | 45 | 7 | 30 | 55/- |
| 25 | 1" | 25 | 30 | 2.5 | 0.30 | 55 | 7 | 30 | 68/- |
| 30 | 1 1/4" | 31 | 36 | 2.5 | 0.40 | 75 | 6.5 | 30 | 92/- |
| 40 | 1 1/2" | 38 | 43 | 2.5 | 0.50 | 95 | 5 | 30 | 115/- |
| 50 | 2" | 50 | 57 | 3.5 | 0.73 | 120 | 4 | 30 | 170/- |
| 65 | 2 1/2" | 63 | 71 | 4 | 1.06 | 160 | 4 | 30 | 250/- |
| 75 | 3"? | 75 | 84 | 4.5 | 1.40 | 270 | 3.5 | 30 | 330/- |
| 90 | 3 1/2" | 90 | 99 | 4.5 | 1.66 | 290 | 3.5 | 30 | 500/- |
| 100 | 4" | 101 | 112 | 5.5 | 2.50 | 310 | 3.5 | 30 | 550/- |
| 110 | 4 1/2" | 110 | 121 | 5.5 | 3.30 | 330 | 3.5 | 15 | 850/- |
| 125 | 5" | 126 | 139 | 6.5 | 3.66 | 340 | 3 | 15 | 925/- |
| 150 | 6" | 152 | 167 | 7.5 | 5.00 | 350 | 2.5 | 15 | 1150/- |
| 200 | 8" | 203 | 221 | 9 | 8.30 | 400 | 2.5 | 6 | 2100/- |