




SOLAR STUDS

Sr.no	Picture	Product Name	Product Code	Specification	HSN Code	GST%	Price (Rs.)
1		SOLAR ROAD STUD (WITHOUT SHANK)- IMPORTED	AXN-SS-W/O-SHANK-RED-I	MATERIAL: CAST ALUMINIMUM & PLASTIC PC REFLECTOR... HEIGHT: 105X105X25 MM SOLAR PANEL: 2V/120 MA (MONO CRYSTALLINE SILICON) MAINTENANCE POWER: 1.2V/600 MAH MODE: FLASHING LED:- 3PCS EACH SIDE (TTL 6 NOS LED) STANDBY TIME: 72 Hrs. ONCE FULLY CHARGED WORKING TEMP.: 20DEGREE +80 DEGREE C VISUAL RANGE: 500MTRS WEIGHT: 330 GRM WATER RESISTENCE: WATERPROOF IP 68	85308000	18%	1250/PC
2		SOLAR ROAD STUD (WITHOUT SHANK) - INDIAN	AXN-SS-W/O-SHANK-RED-L	MATERIAL: CAST ALUMINIMUM & PLASTIC PC REFLECTOR... HEIGHT: 105X105X25 MM SOLAR PANEL: 2V/120 MA (MONO CRYSTALLINE SILICON) MAINTENANCE POWER: 1.2V/600 MAH MODE: FLASHING LED:- 3PCS EACH SIDE (TTL 6 NOS LED) STANDBY TIME: 72 Hrs. ONCE FULLY CHARGED WORKING TEMP.: 20DEGREE +80 DEGREE C VISUAL RANGE: 500MTRS WEIGHT: 330 GRM WATER RESISTENCE: WATERPROOF IP 68	85308000	18%	1375/PC
3		SOLAR ROAD STUD (WITHOUT SHANK) - IMPORTED	AXN-SS-W/O-SHANK-YELLOW-I	MATERIAL: CAST ALUMINIMUM & PLASTIC PC REFLECTOR... HEIGHT: 105X105X25 MM SOLAR PANEL: 2V/120 MA (MONO CRYSTALLINE SILICON) MAINTENANCE POWER: 1.2V/600 MAH MODE: FLASHING LED:- 3PCS EACH SIDE (TTL 6 NOS LED) STANDBY TIME: 72 Hrs. ONCE FULLY CHARGED. WORKING TEMP.: 20DEGREE +80 DEGREE C VISUAL RANGE: 500MTRS WEIGHT: 330 GRM. WATER RESISTENCE: WATERPROOF IP 68	85308000	18%	1250/PC

4		SOLAR ROAD STUD (WITHOUT SHANK) - INDIAN	AXN-SS- W/O- SHANK- YELLOW- L	MATERIAL: CAST ALUMINIMUM & PLASTIC PC REFLECTOR... HEIGHT: 105X105X25 MM SOLAR PANEL: 2V/120 MA (MONO CRYSTALLINE SILICON) MAINTENANCE POWER: 1.2V/600 MAH MODE: FLASHING LED:- 3PCS EACH SIDE (TTL 6 NOS LED) STANDBY TIME: 72 Hrs. ONCE FULLY CHARGED. WORKING TEMP.: 20DEGREE +80 DEGREE C VISUAL RANGE: 500MTRS WEIGHT: 330 GRM. WATER RESISTENCE: WATERPROOF IP 68	85308000	18%	1375/PC
5		SOLAR ROAD STUD (WITH SHANK)	SOLAR STUD WITH SHANK - RED	MATERIAL: POLYCRBONATE, ALUMINIMUM SIZE: 128X134X23 MM ELECTRONICS: SOLAR PANEL 3.25 V/ 130 MA BATTERY: 1.2 V/ 1800 MAH NIMH LED: 6 NOS. (SUPER LUMINOSITY LED) VISIBILITY: 40 MTRS FLASHING RATE: AROUND 60 - 100 TIMES / MINUTE AS REQUIRED REFLECTOR: PRISMATIC, REFLECTOR (2 WAY REFLECTIVE)	85308000	18%	1375/PC
6		SOLAR ROAD STUD (WITH SHANK)	SOLAR STUD WITH SHANK - YELLOW	MATERIAL: POLYCRBONATE, ALUMINIMUM SIZE: 128X134X23 MM ELECTRONICS: SOLAR PANEL 3.25 V/ 130 MA BATTERY: 1.2 V/ 1800 MAH NIMH LED: 6 NOS. (SUPER LUMINOSITY LED) VISIBILITY: 40 MTRS FLASHING RATE: AROUND 60 - 100 TIMES / MINUTE AS REQUIRED REFLECTOR: PRISMATIC, REFLECTOR (2 WAY REFLECTIVE)	85308000	18%	1375/PC
7		Polycarbonate Solar Road Studs With Single Shank 360 Degree Illumination 6 Months Warranty. To be Installed only on the Edges & Medians of the Roads	Solar Studs With Single Shank	MATERIAL: POLYCRBONATE, SIZE: 135 MM DIA / 25 MM THICKNESS ELECTRONICS: SOLAR PANEL 3.25 V/ 130 MA BATTERY: 1.2 V/ 1800 MAH NIMH LED: 8 NOS. (SUPER LUMINOSITY LED) VISIBILITY: 100 MTRS FLASHING RATE: AROUND 60 - 100 TIMES / MINUTE AS REQUIRED REFLECTOR: 8 NOS OF 3M REFELCTIVE TAPE FOR REFELCTION	85308000	18%	1625
TERMS & CONDITIONS:-							
Above Prices are Ex works Prices							
Box Packing Included							
Gst - 18% Extra							
Local Freight Charges is Applicable							
Payment - 100% Advance							
No Warranty on Any of the Products							
Damaged Caused in Transport is not our Responsibility							
Special Rates will be given for Bulk Quantity							