

SPARK[®] POLYURETHANE COPPER COATED STEEL HOSE WIRE REINFORCED HOSE



APPLICATIONS:

- For Extraction Arms & Dust Collection Equipment
- For Computer Numerical Control(CNC) Machining Areas
- For Abrasive Solids Such as Dust, Powder, Fibers & Chip
- For Industrial Air Movement Fume Control

PROPERTIES:

- Optimized Flow Properties
- Microbe & Hydrolysis Resistant
- Chemical Resistant
- Good Resistant to UV & Ozone
- Excellent Low Temperature Flexibility
- Small Bending Radius
- Kink-Proof
- Gas & Liquid Tight
- Good Resistant to Abrasion
- Excellent Compressibility 4:1
- Anti-Static by Grounding the Spiral

TEMP RANGE:

- -40°C Approx to + 90°C Approx
- Short Time +125°C Approx

STANDARD COLOR:

- Transparent

CONSTRUCTION:

- Spring Steel Wire Integrated in Wall

MATERIAL:

- Wall: Ester-Polyurethane
- Spiral: Spring Steel Wire

SIZE ID (MM)	STANDARD LENGTH (MTR)	PRICE PER MTR
25	20	495/-
30	20	550/-
40	20	670/-
51	20	770/-
60	20	880/-
63	20	900/-
76	20	975/-
80	20	1000/-
90	20	1050/-
102	20	1075/-
110	15	1265/-
115/120	15	1320/-
127	15	1320/-
140	15	1430/-
152	15	1580/-
160	15	1760/-
165	15	1815/-
175	15	1955/-
180	15	1955/-
203	15	2130/-
220/225	15	2585/-
254	15	2820/-
305	15	3120/-
354	10	3920/-
405	10	5600/-