

SOLAR CONNECTORS



PV CABLE CONNECTOR

ESC-4-X

Type	: Ø4mm PV Connector
Rated Current	: 4 & 6sqmm : 30A 2.5sqmm : 25A
Rated Voltage	: 1500V DC
Contact Resistance	: ≤0.35mOhms
Operating Temperature	: -40°C TO +85°C
Approvals	: TUV
Degree of protection(Mated)	: IP68 (IEC 60529)
Reference Standard	: IEC 62852:2014



ESC-4-UW-X

Type	: Ø4mm With Safety Window
Rated Current	: 4 & 6sqmm : 30A 2.5sqmm : 25A
Rated Voltage	: 1500V DC
Contact Resistance	: ≤0.35mOhms
Operating Temperature	: -40°C TO +85°C
Approvals	: TUV
Degree of protection(Mated)	: IP68 (IEC 60529)
Reference Standard	: IEC 62852:2014



ESC-4-PM-X

Type	: Ø4mm Panel Mount
Rated Current	: 4 & 6 sq mm: 30A 2.5sqmm: 25A
Rated Voltage	: 1500V DC
Contact Resistance	: ≤0.35mOhms
Operating Temperature	: -40°C TO +85°C
Approvals	: TUV
Degree of protection(Mated)	: IP68 (IEC 60529)
Reference Standard	: IEC 62852:2014



BRANCH CONNECTOR



ESC-BC-S1P2,ESC-BC-S2P1


Type	: Ø4mm 2 Way PV
Rated Current	: 30A
Rated Voltage	: 1500V DC
Contact Resistance	: ≤0.5mOhms
Operating Temperature	: -40°C TO +85°C
Approvals	: TUV
Degree of protection(Mated)	: IP68
Reference Standard	: IEC 62852:2014



SOLAR CONNECTORS

PLUS CONNECTOR

(Over moulded)



ESP-PC-X SERIES

Rated Current	: 20A-30A.
Rated Voltage	: 1500V DC
Mounting	: NA
Operating Temperature	: -40°C TO +85°C
Approvals	: NA
Degree of protection(Mated)	: IP67
Reference Standard	: IEC 62852:2014

T CONNECTOR

(Over moulded)



ESP-TC SERIES

Rated Current	: 20A-30A.
Rated Voltage	: 1500V DC
Mounting	: NA
Operating Temperature	: -40°C TO +85°C
Approvals	: NA
Degree of protection(Mated)	: IP67
Reference Standard	: IEC 62852:2014

Y CONNECTOR

(Over moulded)

ESP-YC

Rated Current	: 20A-30A.
Rated Voltage	: 1500V DC
Mounting	: NA
Operating Temperature	: -40°C TO +85°C
Approvals	: NA
Degree of protection(Mated)	: IP67
Reference Standard	: IEC 62852:2014

