



AGGREGATE METERING

EAM-S642A-DE336VX

- Rated Current : 32 Amps
- Rated Voltage : 1 Φ , 230VAC
- Mounting : Vertical (0U) Rack Mounting
- Outlet Socket : IEC-60320 C13 (36 Nos.)
& IEC-60320 C19 (06 Nos.)
- Operating Temp. : 0-45°C (Extended up to 65°C)
- Display : LCD
- Marking : CE, cULus
- Approvals : cULus



AGGREGATE METERING INDIVIDUAL SWITCHING

EAS-S624D-DE310VX

- Rated Current : 32 Amps
- Rated Voltage : 1 Φ , 230VAC
- Mounting : Vertical (0U) Rack Mounting
- Outlet Socket : IEC-60320 C13 (21 Nos.)
& IEC-60320 C19 (03 Nos.)
- Operating Temp. : 0-45°C (Extended up to 65°C)
- Display : LCD



INDIVIDUAL METERING

EIM-T624D-EE336VX

- Rated Current : 32 Amps
- Rated Voltage : 3 Φ , 440VAC
- Mounting : Vertical (0U) Rack Mounting
- Outlet Socket : IEC-60320 C13 (21 Nos.)
& IEC-60320 C19 (03 Nos.)
- Operating Temp. : 0-45°C (Extended up to 65°C)
- Display : LCD
- Marking : CE, cULus
- Approvals : cULus





INDIVIDUAL METERING INDIVIDUAL SWITCHING

EIS-T630A-EE336VX

Rated Current : 32 Amps
 Rated Voltage : 3 Φ , 440V AC
 Mounting : Vertical (0U) Rack Mounting
 Outlet Socket : IEC-60320 C13 (24 Nos.)
 & IEC-60320 C19 (06 Nos.)
 Operating Temp. : 0-45°C (Extended up to 65°C)
 Display : LCD
 Marking : CE, cULus
 Approvals : cULus



POWER MEASUREMENT DEVICE

ED-PT672-XE3X

Rated Current : 32 Amps
 Rated Voltage : 3 Φ , 440V AC
 Mounting : Horizontal (1U) Rack Mounting
 Outlet Socket : 72 Channels
 Operating Temperature : 0-45°C (Extended up to 65°C)
 Display : LED



ENVIRONMENT MONITORING DEVICE

EMD-TH1W1S1D1-BS

Rated Current : 16 Amps
 Rated Voltage : 1 Φ , 230VAC
 Mounting : Horizontal (1U) Rack Mounting
 Number of Sensors : Digital Sensor Ports - 08 Nos
 Analog sensor Ports - 04 Nos
 Operating Temperature : 0-45°C (Extended up to 65°C)
 Display : LCD



SINGLE INLINE METER

EIN-T6A3-2AK-2AJH

Rated Current : 132 Amps
 Rated Voltage : 3 Φ , 440V AC
 Mounting : Horizontal (1U) Rack Mounting
 Outputs : 01 Nos(3 Φ , 32Amps, IEC 60309
 (3P+N+E) Ind. Socket, 440VAC)
 Operating Temperature : 0-45°C (Extended up to 65°C)
 Display : LED

