

Available in 10/13 Shank Allen Screw for Easy Drill ejection

Special Tungsten Carbide

Easy Slug Removal

High Quality HSS Drill

# Characteristic

- Easy drilling in work materials of up to 4mm (5/32") thickness.
- By attaching this tool to an electric drill with high rotational speed, Much faster drilling is possible compared to high speed steel cutters.

# **Applications**

- Aluminium, Copper, Brass, Mild Steel, I Beam etc. of up to 4mm (5/32") thinkness in combination with HSS Center drill.
- FRP Plates , Hardened Steel, Stainless Steel, Resin Plates, etc. of up to 4mm (5/32") thickness in combination with Carbide Tip Center Drill

### Specifications

Ø12mm to Ø120mm Cutter Size :

Max. drilling depth: 4mm (5/32")

Center drill: HSS Center drill, Carbide

tipped Center drill

Shank size: Shank size:

Applicable electric drill: Portable electric drills (in the

rotary-only mode) Not for

#### Silver Series Carbide Hole Saw Cutters

Sr. No.	Size	Price	Package Type
1	14 MM	325/-	PLASTIC CASE
2	16 MM	365/-	PLASTIC CASE
3	19 MM	435/-	PLASTIC CASE
4	22 MM	500/-	PLASTIC CASE
5	25 MM	570/-	PLASTIC CASE
6	29 MM	660/-	PLASTIC CASE
7	32 MM	730/-	PLASTIC CASE
8	35 MM	795/-	PLASTIC CASE
9	38 MM	865/-	PLASTIC CASE
10	44 MM	1000/-	PLASTIC CASE
11	51 MM	1160/-	PLASTIC CASE
12	54 MM	1230/-	PLASTIC CASE
13	57 MM	1300/-	PLASTIC CASE
14	64 MM	1455/-	PLASTIC CASE
15	70 MM	1590/-	PLASTIC CASE
16	76 MM	1730/-	PLASTIC CASE

Minimum Order Quantity 10 Pieces

# Safety Instruction





